



DIESEL 10000 E SILENCE UK

PORTABLE POWER

Generating Sets Range DIESEL

PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- KOHLER air-cooled industrial engine
- Very Silent
- Soundproofing and against shocks panels
- Hydrocarbons bulk tank

This genset is quiet and compact and features easy-to-reach components for simplified maintenance. The Mics MODYS control panel displays overspeed, starting failure, oil pressure, battery and temperature

Range DIESEL

Both long run times and very long life for professional applications.



This product meets the Qualigen charter, which aims to ensure a high level of quality and guarantee the safety of users. Qualigen: commitment to safety and quality.

DIESEL 10000 E SILENCE UK

GENERAL SPECIFICATIONS

Range	DIESEL
Frequency (Hz)	50
Max power LTP (kW) *	9
Nominal voltage (V)	230
Number of Phase	Single phase
Fuel	Fuel
Tank (L)	27
75% cons. (l/h) *	2.10
75% Autonomy (h) *	12.90
Sound power level guaranteed LwA dB(A)	97
Acoustic pressure level @1m in dB(A)	81
Acoustic pressure level @7m in dB(A)	68

ENGINE SPECIFICATIONS

Engine model	KOHLER DIESEL
Engine type	KD425-2
Distribution	Diesel O.H.V.
Start	Electrical
Oil Guard	Oui
Capacity (cm3)	851
Oil capacity (L)	2.60

ALTERNATOR SPECIFICATIONS

Technology	Without collar or brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

2 115V 16A sockets - circuit breaker + 2 115V 32A sockets - circuit breaker + 2 230V 16A sockets - circuit breaker + 1 230V 32A socket - circuit breaker + hour meter + indicator + MICS MODYS

DIMENSIONS AND WEIGHT

Length (cm)	118.30
Width (cm)	67.30
Height (cm)	96
Dry Weight (kgs)	271

PACKAGING

Packaging type	Box
Length (cm)	120
Width (cm)	69
Height (cm)	94
Weight (kg)	274
Pallet type	
Number of box by pallet	0
Pallet height (cm)	0
weight of the packaged Pallet (kg)	0



ACCESSORIES SUPPLIED



User and maintenance manual



Lifting eye



Battery without maintenance

Hour meter

OPTIONS



RSTART

Wireless remote

Remote control in order to start or stop the generating set until a distance of 50 meters (needs the installation of a MODYS control panel)



VERSO50

Automatic start panel

Switches over automatically if the mains fails, 40A or 100A 1P or if the mains fails, 25A or 40A 3P (needs the installation of a MODYS control panel). Includes the battery charger.



R05M

Manual changeover switch

The manual changeover switch is used to connect and disconnect a generating set manually to a domestic circuit when there is a power cut.



RKB5

Trolley kit

Trolley kit with 1 handle and 2 solid tyres for Diesel 10000 E SILENCE et Diesel 15000 TE SILENCE gensets

no picture

RKDS3

Maintenance kit

Maintenance kit for KOHLER KD425-2 engine.



RPQ

Earth spike

For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.