



## DIESEL 6500 TE XL C

PORTABLE POWER

Generating Sets Range DIESEL

### PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- KOHLER air-cooled industrial engine
- Large Autonomy
- Comfort of prehension thanks to the ergonomic handles
- Electric starter with batteries without maintenance

**OIL SAFETY** Thanks to this functionality, the engine will not start or will stop during its functioning if the oil level for gasolines or the oil pressure for diesels is too low : your generating set is perfectly protected !

### Range DIESEL

Both long run times and very long life for professional applications.



## DIESEL 6500 TE XL C

### GENERAL SPECIFICATIONS

Range	DIESEL
Frequency (Hz)	50
Max power LTP (kW) *	5.20
Max power LTP (kVA)	6.50
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Fuel
Tank (L)	16
75% cons. (l/h) *	1.20
75% Autonomy (h) *	13.30
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	93.15462905419090
Acoustic pressure level @7m in dB(A)	78.795881787498

### ENGINE SPECIFICATIONS

Engine brand	KOHLER DIESEL
Engine ref.	KD440E
Distribution	Diesel O.H.V.
Start	Electrical
Low Oil pressure shutdown	Oui
Displacement (cm3)	442
Oil capacity (L)	1.50

### ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H

### PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

### DIMENSIONS AND WEIGHT

Length (cm)	81
Width (cm)	55.50
Height (cm)	59
Dry Weight (kgs)	108

### PACKAGING

Packaging type	Box
Length (cm)	82
Width (cm)	56.50
Height (cm)	60
Weight (kg)	111
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	193
weight of the packaged Pallet (kg)	676



3/15/2016

DIESEL 6500 TE XL C - PORTABLE POWER - Generating Sets DIESEL

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. \*ISO 8528.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

## ACCESSORIES SUPPLIED



User and maintenance manual



Floor maintaining slot




Ergonomic handle grip



Battery without maintenance

## OPTIONS



R03

R03

This set includes the hour meter and the differential circuit breaker.

3499231  
002575

RKB1HD

ERR:not found in dict valeurs

no picture

3499231  
001745

RKDS1

Maintenance kit for KOHLER CH350E and CH440E engines (Diesel 6000 E XL C - Diesel 6500 TE XL C).



RH1

RH1

Cover for SDMO 's generating sets, welding sets and water pumps



RPM

RPM

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ

RPQ

For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm<sup>2</sup> cable.



RBAC

RBAC

Removable storage box