



HX 7500 T S

PORTABLE POWER

Generating Sets Range INTENS

PRODUCT ADVANTAGES

- Entire group guaranteed 3 years
- HONDA Professional Engine
- Solid and high-performance equipment

Range INTENS

Equipment that is robust, long-lasting and simple to use for repetitive operations in difficult conditions.



HX 7500 T S

GENERAL SPECIFICATIONS

Range	INTENS
Frequency (Hz)	50
Max power LTP (kW) *	6
Max power LTP (kVA)	7.50
Nominal voltage (V)	400
Number of Phase	Three phase
Fuel	Petrol
Tank (L)	6.10
75% cons. (l/h) *	2.50
75% Autonomy (h) *	2.40
Sound power level guaranteed LwA dB(A)	103
Acoustic pressure level @1m in dB(A)	88.23717842803190
Acoustic pressure level @7m in dB(A)	73.81151590981260

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX390
Distribution	O.H.V.
Start	Starter
Low Oil pressure shutdown	Oui
Displacement (cm ³)	389
Oil capacity (L)	1.10

ALTERNATOR SPECIFICATIONS

Technology	Collar and brush
AVR Regulation	No
Indication of protection	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	71.50
Width (cm)	57
Height (cm)	59
Dry Weight (kgs)	76

PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	59.50
Weight (kg)	78.50
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	191.50
weight of the packaged Pallet (kg)	481



HX 7500 T S - PORTABLE POWER - Generating Sets INTENS

3/15/2016

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products. *ISO 8528.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

ACCESSORIES SUPPLIED



Funnel



User and maintenance manual

OPTIONS



R03

R03

This set includes the hour meter and the differential circuit breaker.



RKB2

RKB2

Trolley kit for the generating sets superior to 6kW



RH1

RH1

Cover for SDMO 's generating sets, welding sets and water pumps



RPM

RPM

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ

RPQ

For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.